
Standard Taps--High Speed Steel Spiral Point, Fluteless, GH3, Plug

Fluteless spiral pointed taps are recommended for production tapping of through holes in thin sections not greater than one diameter in thickness. The fluteless spiral pointed tap was developed to produce a tap of maximum strength—it has spiral points only; the tap body is threaded without flutes. This design of tap offers maximum rigidity required to minimize breakage caused by misalignment. These taps have proven very successful in the tapping of sheet metal.



Tap Description	Part Number	Price
4-40 H2	117717	15.25
5-40 H2	118072	15.25
6-32 H3	118527	13.07
8-32 H3	119155	13.07
10-24 H3	119763	13.07
10-32 H3	120297	13.07
12-24 H3	120558	13.07
1/4-20 H3	121113	13.07
5/16-18 H3 2/sppt	122130	14.82
5/16-18 H3 3/sppt	122142	14.82
3/8-16 H3	123020	17.44
7/16-14 H3	123754	23.71
1/2-13 H3	124424	31.30

Standard Taps--Spiral Point Extensions--6" Overall Length, H3, Plug Style High Speed Steel



Tap Description	Part Number	Price
6-32 H3 2FL	273946	59.34
8-32 H3 2FL	273958	59.34
10-32 H3 2FL	273960	52.74
1/4-20 H3 2FL	271159	50.68
5/16-18 H3 2FL	271172	52.74
3/8-16 H3 3FL	271160	59.34



Telephone 800-258-7162 or 603-332-9000
Fax 1-603-332-8069
